



HIGH PERFORMANCE AUTOMATIC TRANSMISSION FLUID

SPECIFICATIONS

GM Dexron III H

DESCRIPTION

Ola ATF III H is a high performance fluid for automatic transmissions vehicles specifying Dexron III H. It is also used as a hydraulic fluid in unique applications.

FEATURES AND BENEFITS

Ola ATF III H is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antioxidants, and defoamers providing outstanding performance:

- Good thermal and oxidation stability.
- Good anti-wear properties.
- Meets the wear requirement to promote longer transmission life.
- Excellent low-temperature fluidity.
- Effective foam control properties.
- Compatible with all common seal materials used in Type III G transmissions.

APPLICATIONS

Ola ATF III H is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying Dexron III H level performance as well as the related power steering systems.

Ola ATF III H is also suitable for Off-highway transmissions power steering and other hydraulic systems requiring a Dexron III H.



TYPICAL PROPERTIES

	Test Method	ATF III H
Viscosity @ 100°C – cSt	ASTM D 445	7.5
Viscosity Index	ASTM D 2270	Min 170
Pour Point °C	ASTM D 97	-44
Flash Point °C	ASTM D 92	200
Density @ 15°C - kg/l	ASTM D 4052	0.870

The characteristic values appeared on the top in the table are typical values given only as an indication.

HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.