



Accel XL 5 SAE 40,50



MONOGRADE ENGINE OIL

SPECIFICATIONS

API SG/CF

DESCRIPTION

Accel XL5 is monograde engine oil for use in car engines and commercial vehicles. It is formulated from high quality mineral base oils and an advanced additive system to provide superior performance.

FEATURES AND BENEFITS

- Improve engine cleanliness from a combination of detergents and dispersants.
- Control the build-up of sludge and deposits.
- Good protection against wear and corrosion.
- Low oil consumption, and longer intervals between oil change.

APPLICATIONS

Accel XL5 is recommended for all car engines as well as commercial vehicles requiring performance level API SG/CF.

TYPICAL PROPERTIES

	Test Method	Accel XL5 40	Accel XL5 50
Grade SAE		40	50
Viscosity @ 40°C - cSt	ASTM D 445	138	250
Viscosity @ 100°C - cSt	ASTM D 445	14.8	20.9
Indice de viscosité	ASTM D 2270	99	98
TBN - mg KOH/g	ASTM D 2896	9.3	9.3
Flash point °C	ASTM D 97	- 12	- 12
Pour point °C	ASTM D 92	254	260
Density @ 15°C - kg/l	ASTM D 4052	0,887	0,892

The characteristic values appeared on the top in the table are typical values given only as an indication.



Accel XL 5 SAE 40,50



HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.