



# Agrol Super 15W-40



## SUPER TRACTOR OIL UNIVERSAL

### SPECIFICATIONS

- API CG-4/SF
- API GL-4
- ACEA E3
- ZF TE ML 06A, B, C and 07B
- Ford M2C 159B/C - Ford M2C 134D
- New Holland 82009201/3
- CASE New Holland MAT 3525 and 3526
- John Deere J27/J20C
- Massey Ferguson CMS M 1135,1139, 1143,1144 &1145

### DESCRIPTION

Agrol Super 15W-40 is high performance STOU working in severe conditions recommended for use in the following systems in farm tractors and implements: Crankcase of diesel and four stroke gasoline engines , Hydraulics, transmissions, wet brakes, power take offs, hydrostatics and power steering.

### FEATURES AND BENEFITS

Agricultural enterprises employ a wide variety of equipment requiring multi-functional lubrication performance. The engineering in Agrol Super15W-40 meets the diverse lubrication requirements of this equipment which reduces the number of lubricants required and the possibility of misapplication. The key benefits include:

- Good thermal and oxidation stability.
- Reduced sludge build-up and high temperature deposits.



# Agrol Super 15W-40



- TBN reserves Improved deposit control.
- Good rust and corrosion protection.
- Reduced wear and longer equipment life especially in hydraulic components.
- Effective detergency/dispersancy Cleaner engines and longer engine life.
- High temperature viscosity retention and volatility control.
- Reduced engine scuffing, bore polishing, and oil consumption.

## APPLICATIONS

- Mixed diesel and gasoline-powered farm vehicles and equipment.
- Farm equipment transmissions and power systems requiring multifunctional fluid.

## TYPICAL PROPERTIES

	Test Method	Agrol Super 15W-40
<b>Grade SAE</b>		15W-40
Viscosity @ 40°C - cSt	ASTM D 445	103.7
Viscosity @ 100°C - cSt	ASTM D 445	14.9
Viscosity Index	ASTM D 2270	138
Pour Point °C	ASTM D 97	-27
Flash point °C	ASTM D 92	230
Density @ 20°C - kg/l	ASTM D 4052	0.88

The characteristic values appeared on the top in the table are typical values given only as an indication.

## HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.