



DeoMax DM 5 SAE 30, 40, 50



HIGH PERFORMANCE MONOGRADE ENGINE OIL

SPECIFICATIONS

API CF

DESCRIPTION

DeoMax DM5 SAE 30, 40, 50 are a high performance monograde oils formulated with a mixture of high performance base oils and balanced additive system. These products are conceived especially for turbo-charged diesel engines and natural aspirated working under severe operating conditions such as on and off - highways segments.

FEATURES AND BENEFITS

DeoMax DM5 SAE 30, 40, 50 provide the potential advantages below:

- Protection against engine's wear.
- Extend deposits control.
- Advanced detergency/dispersency and extend engine life.

APPLICATIONS

- Naturally aspirated and turbo-charged diesel powered equipment.
- Light and Heavy-Duty Trucks and diesel powered equipment in the construction, mining, quarrying, and agriculture industries.



TYPICAL PROPERTIES

	Methods	DM 5 SAE 30	DM 5 SAE 40	DM 5 SAE 50
Grade SAE		30	40	50
Viscosity @ 40°C – cSt	ASTM D 445	90	138	199
Viscosity @ 100°C – cSt	ASTM D 445	10.8	14.0	17.8
Viscosity Index	ASTM D 2270	104	98	97
TBN – mg KOH/g	ASTM D 2896	7.3	7.3	7.3
Pour Point °C	ASTM D 97	- 12	-12	-12
Flash point°C	ASTM D 92	246	270	278
Density @15°C – kg/l	ASTM D 4052	0.879	0.882	0.886

The characteristic values appeared on the top in the table are typical values given only as an indication.

HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.