



HIGH PERFORMANCE MULTIGRADE DIESEL ENGINE OIL

Specification

API CF-4/SJ

Description

DeoMax DM7 is high performance oil for diesel engine working in severe conditions. DeoMax DM7 is recommended for variety of engines: on-highway light and heavy trucking and off highway engines: construction, mining, quarrying, and agriculture.

Features and Benefit

DeoMax DM7 is a high technology oil and particularly efficient in modern diesel engines and older conception engine. It provides the potential advantage below:

- Control of deposits build-up.
- Excellent cleanliness properties and extend engine life.
- Reduce oil consumption and engine wear.

Applications

- Natural aspirated and turbo-charged diesel engines.
- On-highway light and heavy-duty.
- Off highway industries including: construction, mining, quarrying, and Agriculture.



Typical Properties

Grade SAE	Test Methods	DeoMax DM7 SAE 20W-50
Grade SAE		20W-50
Viscosity @ 40°C - cSt	ASTM D 445	138
Viscosity @ 100°C - cSt	ASTM D 445	18
Viscosity Index	ASTM D 2270	120
TBN mg KOH / g	ASTM D 2896	8.5
Pour Point °C	ASTM D 97	-27
Flash point °C	ASTM D 92	228
Density @ 15°C - kg/l	ASTM D 4052	0.879

* The characteristic values appeared on the top in the table are typical values given only as an indication.

Health and Safety

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.