



## HIGH PERFORMANCE MONOGRADE ENGINE OIL

### SPECIFICATIONS

API CF/SL

### DESCRIPTION

DeoMax DM5 PLUS SAE 50 is a high performance monograde oil formulated with a mixture of high performance base oils and balanced additive system. This product is conceived especially for turbo-charged diesel engines and natural aspirated that working in off / on highway under severe operating conditions

### FEATURES & BENEFITS

DeoMax DM5 PLUS SAE 50 provide the potential advantages below:

- Protection against engine's wear.
- Extended oil drain interval.
- Extend deposits control.
- Advanced detergency/dispersency and extend engine life.

### APPLICATIONS

- Naturally aspirated and turbo-charged diesel powered equipment.
- Light and Heavy-Duty Trucks and diesel powered equipment in the construction, mining, quarrying, and agriculture industries.



## TYPICAL PROPERTIES

	Methods	DM 5 PLUS SAE 50
Grade SAE		50
Viscosity @ 40°C - cSt	ASTM D 445	200
Viscosity @ 100°C - cSt	ASTM D 445	19.7
Viscosity Index	ASTM D 2270	99
TBN - mg KOH/g	ASTM D 2896	10
Pour Point °C	ASTM D 97	-9
Flash point °C	ASTM D 92	278
Density @ 15°C - kg/l	ASTM D 4052	0.886

The characteristic values appeared on the top in the table are typical values given only as an indication.

## HEALTH & SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.