



## DeoMax HD50



### HIGH PERFORMANCE MONOGRADE ENGINE OIL

#### Specifications

API CD

#### Description

DeoMax HD 50 is a high performance monograde oil formulated with a mixture of high performance base oils and balanced additive system. The product is designed natural aspirated diesel engines and also turbo-charged diesel engines that working under severe operating conditions such as on and off highways application.

#### Features and Benefits

DeoMax HD 50 provides the below advantages :

- Protection against engine wear
- Extend deposits control
- Advanced detergency / dispersency and extend engine life

#### Applications

- Natural aspirated and turbo-charged diesel engines
- Off highway industries including : construction, mining, quarrying, and agriculture
- On-highway light and heavy-duty



## Typical Properties

	Test Method	DeoMax HD 50
Grade SAE		50
Viscosity @ 40°C - cSt	ASTM D 445	232
Viscosity @ 100°C - cSt	ASTM D 445	19.5
Viscosity Index	ASTM D 2270	98
TBN - mgKOH/g	ASTM D 2896	6
Pour Point °C	ASTM D 97	-6
Flash point °C	ASTM D 92	234
Density @ 15°C - kg/l	ASTM D 4052	0.89

The characteristic values appeared on the top in the table are typical values given only as an indication.

## Health and Safety

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.