



## SPECIFICATIONS

API GL-5

## DESCRIPTION

Ola Gear Oil BV 75W-80 is a premium automotive gear lubricants formulated from high quality base oils and an optimum balanced additive system especially for Hypoid axles, enclosed gearboxes and manual gearboxes demanding performances defined by API GL-5 in the 75W-80 grade.

## PERFORMANCES

Ola Gear Oil BV 75W-80 are designed to meet the demands of heavy-duty applications where high torque, heavy loads, shock loads occur and limited slip capability. They provide protection of gearboxes under severe operating conditions. Their benefits are:

- Excellent oxidation stability that extends gear and bearing life.
- Good Gear protection.
- Excellent rust and corrosion characteristics.
- Effective low temperature lubrication.

## TYPICAL PROPERTIES

Characteristics	Methodes	Unit	Results
Density @ 15°C	ASTM D4052	-	0,856
Cinematic viscosity @ 100°C	ASTM D445	mm <sup>2</sup> /s	8,9
Cinematic viscosity @ 40°C	ASTM D445	mm <sup>2</sup> /s	49,6
Viscosity index	ASTM D2270	-	161
Cinematic viscosity @ 100°C after KRL	CEC L-45-T-93	mm <sup>2</sup> /s	> 8
Viscosity Brookfield @ -40°C	ASTM D2983	mPa.s	passe

The characteristic values appeared on the top in the table are typical values given only as an indication.



## Gear Oil BV 75W-80



### HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.