



HIGH PERFORMANCE TWO-STROKE ENGINE OIL

SPECIFICATIONS

- JASO FA / API TC

DESCRIPTION

Quest 2T is a high performance; two-stroke engine oil for use in motorcycles, snowmobiles and lean/fuel ratio chain saws.

Quest 2 T is pre-diluted to ensure rapid mixing when added to fuel.

FEATURES AND BENEFITS

- Extend engine's life.
- Extend spark and valves use length,.
- Reduce segments pasting and piston's gripping.

APPLICATIONS

Quest 2T is specially recommended for lubrication of two-stroke engines where an API TC/ JASO FA performance is recommended.

TYPICAL PROPERTIES

	Methods	Quest 2T
Viscosity @ 40°C - cSt	ASTM D 445	59.1
Viscosity @ 100°C - cSt	ASTM D 445	9.5
Viscosity Index	ASTM D 2270	110
Flash point °C	ASTM D 92	132
Pour Point °C	ASTM D 97	-12
Density @ 15°C - kg/l	ASTM D 4052	0.874

The characteristic values appeared on the top in the table are typical values given only as an indication.



HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.