



HIGH PERFORMANCE FOUR-STROKE ENGINE OIL

SPECIFICATIONS

- EXCEDE API SL/CF
- JASO (T903): JASO MA/MA-2

DESCRIPTION

Ola Quest 4T SAE 20 W-50 is a mineral based 4-stroke motorcycle oil specially formulated to provide outstanding protection under severe high torque, high stress conditions. Under these conditions, motorcycle engines operate at extremely high temperatures causing viscosity and thermal breakdown of motor oil. Ola Quest 4T provides maximum protection against viscosity and thermal breakdown.

FEATURES AND BENEFITS

- Delivers superior engine wear protection and high film strength for high revving motorcycle engines.
- Specialized additives help prevent ring sticking and build-up of harmful deposits.

APPLICATIONS

Specially designed for use in the 4-stroke motorcycle engines, which require JASO MA/MA-2 performance.



TYPICAL PROPERTIES

	Methods	Quest 4T
Viscosity @ 100°C - cSt	ASTM D 445	20W-50 18.4
Viscosity Index	ASTM D 2270	95
TBN mgKOH/g	ASTM D 2896	7.2
Pour Point °C	ASTM D 97	-12
Density @ 20°C - kg/l	ASTM D 4052	0.89

The characteristic values appeared on the top in the table are typical values given only as an indication.

HEALTH AND SAFETY

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of this product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.